













TRINITY

Turnstiles in 2- and 3-arm techniques with slot machine and ticket spender

This access control system with slot machine is equipped with a graphical color display. The clear, comfortable and ergonomic arrangement of the control elements for the customers and the operating personal is especially designed for the required area of operation. The automatic check of available coins for change (Tubenwechsler) and the optional check for paper-stock guarantees a smooth and maintenance free operation. An extra card reader allows access to the facility for own employees and enables special control and service functions to the management.

This product is especially suitable for pay entry to amusement parks, attractions, baths, public showers and restrooms in restaurants. Particularly in areas with high number of tourists a control of the facility usage is given by this product.

- ✓ Maintenance free mechanics with integrated LOGITURN® control for minimal power consumption
- ✓ Large graphical display
- ✓ Life-time Quality
- ✓ Frequency Counter
- ✓ Control of available coins for change
- ✓ Ticket printer
- ✓ Solid money box with security lock
- ✓ Bidirectional operation





Description:

The motorized turnstile TRINITY in 3- and 2-arm technics (suitable for escape path) is entirely made of stainless. The slot machine including coin return unit and ticket printer is especially suitable for public shower, restrooms, baths and amusement parks as well. The integrated counter offers an exact overview of the customer frequency and income.

The cash box is secured by a special safety lock thus the exchange of the money can be handled by a regular employee.

Models

6CTR3AEC: TRINITY 3A CrNi

6CTR2AEC: TRINITY 2A CrNi

Extras

21781-N: Photo-sensor for opening exit
21021TL-N: Ticket printer for Trinity (Leporello)

21021TR-N: Ticket printer for Trinity (paper roll)

2P411-N: Sensor start + light barrier release signal

2P412-N: Sensor start contact free access
2P414-N: Sensor start contact free access light barrier release for LT

Optional:

21024T-N: TRINITY special - personal card

21023T: TRINITY Level Controller

21022T: TRINITY SET break in & manipulation detection

Other products:

21510: Guardrail on platform

21550: Grating platform

Area of application:

- Public restrooms and baths
- Spas
- Amusement parks
- Pay entry
- Attractions
- Indoor and outdoor

Technische Eigenschaften

Power supply	24 V =
Power consumption	50 Wh
Storage temperature	-40°C bis +50°C
Operating temperature	-10°C bis +50°C
width / free width	900mm / 570mm
Length	1.000mm
Height	1.647mm
Set-up area	900mm x 1.000mm
Mass	50kg
Material	CrNi-steel grade 1.4301 = V2A
communication	potential free contacts

