



# ECCO 120 BFB

**Portal turnstile, 120° separation, with barrier-free wheelchair passage**

Especially well suited for outdoor plant access points.

- Barrier-free passage
- Easy assembly and installation
- Vandal-proof
- Single or bidirectional operation
- Reversible entry direction
- High quality and long service life
- Integrated LOGITURN control unit
- Maintenance-free mechanism
- Easily accessible electronics
- Traffic counter

## Functional Description:

The motorized full-height Ecco 120 BFB portal turnstile allows wheelchair passage.

Ecco 120 BFB is especially well suited for outdoor plant access control as well as stadiums, recreation facilities and garage-to-building transitions.

The Ecco 120 BFB is suitable for single or bidirectional operation, and its 120° division means high comfort with good traffic separation.

## Application Areas:

- Building Access Control
- Trade Shows
- Events & Stadiums

## Technical Characteristics:

Power Supply:	230 V AC 50-60 Hz
Power Consumption:	max. 50 VA
Operating Temperature:	-25°C to +40°C
Width / Lane Width:	2.617 mm/620 mm
Length:	1.300 mm
Height:	2.252 mm
Mass:	230 kg
Reader Interface:	Floating Contacts
Material:	CrNi Steel Type 1.4301 Aluminium powder-coated

## Models:

**62265:** Ecco 120 BFB

## Extras/Options:

**63600:** ECCO Roof BASIC, length 1.500 mm

**63630:** ECCO Roof BASIC, length 2.500 mm

**63620:** ECCO Roof COMFORT, length 1.624 mm

**63650:** ECCO Roof COMFORT, length 2.624 mm

**62710:** CrNi Steel Rain Duct

**21775:** Lane Indicator green

**21777:** Lane Indicator red/green

**21781:** Opto-sensor Release

**62199:** Overall Powder-coating in RAL colour

**62813:** Founding assembly kit

**22000:** Power-down blocking kit

## Suitable By-Products:

**21501:** Reader Stand LS 154

**21695:** Reader Stand LS 140

