



# ECCO Arena

**Double portal turnstile,  
90° division  
high traffic separation**

Especially well suited for outdoor entrances to stadiums and in building access control with high demands on mechanical load capacity.

- Card readers can be installed
- Easy assembly and installation
- Vandal-proof
- Single or bidirectional operation
- Reversible entry direction
- High quality and long service life
- Integrated LOGITURN control unit
- Maintenance-free mechanism
- Easily accessible electronics
- Traffic counter

## Functional Description:

The Ecco Arena motorized double portal turnstile with stainless steel drum and barrier grate and galvanized guides and feet is especially well suited for stadiums, high-traffic recreation facilities and also for outdoor building access control.

The front panels can accommodate card readers.

The Ecco Arena is suitable for single or bidirectional operation and its 90° division means very good traffic separation.

## Application Areas:

- Building Access Control
- Trade Shows
- Events & Stadiums

## Technical Characteristics:

Power Supply:	230 V AC 50-60 Hz
Power Consumption:	50 VA max.
Operating Temperature:	-25°C to +40°C
Outer/Inner Width:	2.106 mm / 550 mm
Length:	1.750 mm
Outer/Inner Height:	2.252 mm / 2.050 mm
Weight:	230 kg
Reader Interface:	Floating Contacts
Material:	CrNi-Steel Type 1.4301 Aluminium, powder-coated Hot-galvanized Steel

## Models:

**62260:** Ecco Arena

## Extras/Options:

**63600:** ECCO Roof BASIC, length 1.500 mm

**63630:** ECCO Roof BASIC, length 2.500 mm

**62710:** CrNi Steel Rain Duct

**21775:** Lane Indicator green

**21777:** Lane Indicator red/green

**21781:** Opto-sensor Release

**62198:** Overall Powder-coating in RAL colour

**21699:** Laser-cut cutouts

**62814:** Founding assembly kit

**22000:** Power-down blocking kit

## Suitable By-Products:

**21501:** Reader Stand LS 154

**21695:** Reader Stand LS 140

